


STRUCTURED POLYCARBONATE SHEET



10mm Twinwall

MARLON ST is the multiwall polycarbonate sheet manufactured by Brett Martin. The sheet is characterised by high optical clarity, light transmission, impact resistance and durability. It is available in a range of standard sizes, clear and tinted.

MARLON ST Longlife has a co-extruded UV protection layer on one side.

Colours:	Light Transmission:	
	DIN 5036	
Bronze (B)	33%	
Clear (S)	82%	
Opal (V)	40%	

^{*}Non-standard colours are available subject to minimum order quantities.

Standard sheet sizes:	
Width	2100mm
Length	6 & 7 m (and as required)
Thickness	10mm

^{*}Non-standard colours are available subject to minimum order quantities.

Nominal Sheet Weight	1.7 kg/m ²
U- Value	3.2 W/m ² K

Service Temperature

MARLON ST can be installed in a diversity of applications, with varying temperatures. The material's mechanical performance is known to remain stable in prolonged service in temperatures ranging from -20 to +100 °C.

Installation

Applications of MARLON ST must make adequate allowance for thermal movement, nominally 3.5 mm per metre.

The minimum curve radius for 10 mm Twinwall sheet is 1750 mm.

Fire Performance

The fire performance of MARLON ST has been independently tested. For the most up to date certifications please contact the Technical department.



Brett Martin Ltd. pursues a policy of continuous product development and reserves the right to amend specifications without notice.

Brett Martin Ltd., 24 Roughfort Road, Mallusk, Co. Antrim, N. Ireland, BT36 4RB. Tel: +44 (0)28 9084 9999 Fax: +44 (0)28 9083 6666 E-mail: technical@brettmartin.com